



AGRI S.T.O.U. 10W-40



DESCRIPTION AGRI S.T.O.U. 10W-40 is a semi synthetic lubricant based on carefully selected highly refined base oils for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

APPLICATIONS This oil is recommended for the lubrication of charged and uncharged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment. Anti-wear and oxidation stability: proven protection of critical parts. Cold start: excellent fluidity at low temperature.

SPECIFICATIONS

ACEA	E3	MF	M 1135
ALLISON	C4 (Agriculture applic.)	MF	M 1139
API	GL-4	MF	M 1143
API	CG-4	MF	M 1144
API	GL-5	NH	NH 024C
API	SF/CE	NH	NH 410B
CASE	MAT 3525	NH	NH 420A
CASE	MAT 3526	ZF	TE-ML 03A
FORD	ESN-M2C-159B/C	ZF	TE-ML 05K
FORD	ESN-M2C134 C/D	ZF	TE-ML 06A
FORD	ESN-M2C159 B/C	ZF	TE-ML 06B
FORD	FNH 82009203	ZF	TE-ML 06C
JD	J27	ZF	TE-ML 07B
JD	J20C	ZF	TE-ML 07D
MF	M 1145		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	96
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.1
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Flash Point COC	ASTM D92	°C	220

BELGO-AMERICAN OIL STORAGE N.V BELCO MOTOR OIL.

Wijnegembaan 6, Antwerp – Belgium

E-mail: contact@belcomotoroils.com

Tel: +32 3 658 45 53

www.belcomotoroils.com

BELGO-AMERICAN OIL STORAGE N.V.
Wijnegembaan 6
2900 SCHOTEN
BELGIUM

05/05/2020



CERTIFICATE OF QUALITY

DATE: 15/04/2020		
SUPER TRACTOR AGRI S.T.O.U. 10W-40		
Product Details		ACEA E3 API CF-4/CG-4/GL-4.5 NEW HOLLAND 526C/410B/420A JOHN DEERE J20C/J27 ALLISON C4 FENDT CASE MAT 3525/3526 FORD ESN-M2C134C/D MASSEY FERGUSON M1144/1145
TYPICAL ANALYSIS		
Density at 15°	0.875	
Kinematic viscosity at 40°C	96.0	
Kinematic viscosity at 100°C	14.1	
Viscosity index	150	
Pour point	-36	
CCS viscosity at -25°C	6700	
Flash Point COC	220	

Responsible Analyst: Marcel Verhoeven

Belgo-American Oil Storage NV
Wijnegembaan 6, Antwerp 2900
TEL: +32 3 658 45 53
E-mail: contact@belcomotoroils.com
www.belcomotoroils.com

BELGO-AMERICAN OIL STORAGE N.V.
Wijnegembaan 6
2900 SCHOTEN