



BELCO MOTOR OIL
DRIVING FORCE FOR PERFORMANCE



SAE 75W80 ULTRASYN

Description

SAE 75W80 ULTRASYN gear oil is a universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

Application

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Performance Level

Meets the requirements of
API GL-4/GL-5/MT-1
MIL-L-2105D/MIL-PRF-2105E, SAEJ2360
ZF TE-ML 02B/17B

Typicals

Density at 15 °C, kg/l	0,849
Viscosity 40 °C, mm ² /s	38,30
Viscosity 100 °C, mm ² /s	7,31
Viscosity Index	159
Flash Point COC, °C	194
Pour Point, °C	-60

BELGO-AMERICAN OIL STORAGE N.V
WIJNEGEMBAAN 6 ANTWERP- BELGIUM
BTW: BE 0403 722 908 [Tel: + 32 3 658 45 53](tel:+3236584553)
E mail: info@belcomotoroil.com

www.belcomotoroil.com

Product information 15-08-2017

[Handwritten signature]
Wijnegeembaan 6
Antwerpen
Belgium