



TITANIUM 10W-40 SN/CF



DESCRIPTION TITANIUM 10W-40 is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil is designed for the lubrication of four-stroke petrol and diesel engines of passenger cars and vans. The use of high-quality components ensures that the oil has a great fluidity at low temperature and a stable viscosity at high temperatures. Its low ash formulation is supplemented with an additional anti-oxidant, delivering outstanding performance and long service life.

APPLICATIONS This oil is used for most petrol and diesel engines, both normally aspirated and supercharged. It is particularly recommended for direct-injection diesel engines, such as Common Rail, HDI, CDI, etc. Because of its excellent viscosity index it can be used all year round. It meets the latest requirements from both the American and European car manufacturers. Total engine protection: excellent engine cleanliness and durability. Cold start: very good fluidity at low temperature.

SPECIFICATIONS

ACEA	A3/B3-10	MB	229.3
ACEA	A3/B4-08	VW	502.00/505.00
API	SN/CF	RN	0700/0710
		BMW	LL-01

TYPICAL CHARACTERISTICS

Test	Method	Unit	Results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	93
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.9
Viscosity index	ASTM D2270		153
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6820
Sulfated Ash	ASTM D874	Mass %	1.03
Flash Point COC	ASTM D92	°C	220

BELGO-AMERICAN OIL STORAGE N.V BELCO MOTOR OIL.

Wijnegembaan 6, Antwerp – Belgium

E-mail: contact@belcomotoroils.com

Tel: +32 3 658 45 53

www.belcomotoroils.com

BELGO-AMERICAN OIL STORAGE N.V.

Wijnegembaan 6

2900 SCHOTEN

BELGIUM

10/03/2020



CERTIFICATE OF QUALITY

DATE: 15/06/2018			
SAE 10W40 TITANIUM			
Product Details		API SN/CF ACEA A3/B4-12 VW 505.00/502/00 MB 229.3	
TYPICAL ANALYSIS			
Viscosity at 100°C	13.10		
Density at 15°C	0.872		
Viscosity index	151		
Pour Point	- 39°C		
Flash point	216		

Responsible Analist : Marcel Verhoeven

BELGO-AMERICAN OIL STORAGE
Wijnegembaan 6
2900 SCHOTEN
BELGIUM

**TECHNICAL CUSTOMER
AND LABO SERVICE**

Belgo-American Oil Storage NV
Wijnegembaan 6, B-2900 Schoten
TEL 0032 (0) 3 658 45 53
FAX 0032 (0) 3 658 67 30
info@belcomotoroil.com
www.belcomotoroil.com