



MULTISYN 5W-30 C2/C3



DESCRIPTION MULTISYN 5W-30 is a synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 or C3 engine oils are required. Furthermore, this engine oil has the Renault RN 17 specification level. This means that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil. Broad coverage: reduced lubricant costs. Significant friction reduction: improved fuel efficiency and lowered emissions. Excellent engine cleanliness: outstanding engine protection during the entire oil drain interval.

SPECIFICATIONS

ACEA	C2-16	MB	229.52
ACEA	C3-16	MB	229.31
API	SN	MB	229.51
BMW	LOGLIFE-04	RENAULT	RN17 Level
FIAT	9.55535-S1	VW	505.01
FIAT	9.55535-S3	VW	505.00
GM	dexos2		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.0
Viscosity index	ASTM D2270		167
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.78
Flash Point COC	ASTM D92	°C	225

BELGO-AMERICAN OIL STORAGE N.V. BELCO MOTOR OIL
Wijnegembaan 6, Antwerp – Belgium
E-mail: contact@belcomotoroils.com
Tel: +32 3 658 45 53
www.belcomotoroils.com

BELGO-AMERICAN OIL STORAGE N.V.
Wijnegembaan 6
2900 SCHOTEN

20/03/2020

19-1-2022



CERTIFICATE OF QUALITY

DATE: 05/01/2022		
MULTISYN 5W-30 C2/C3		
Product Details		ACEA C2-16/C3-16 API SN BMW LONGLIFE-04 FIAT 9.55535-S1/S3 GM Dexos 2 MB 229.52/229.31/229.51 RENAULT RN17 Level VW 505.00/505.01
TYPICAL ANALYSIS		
Density at 15°C	0.852	
Kinematic viscosity at 40°C	70.9	
Kinematic viscosity at 100°C	12.0	
Viscosity index	167	
B.N. (HCL04 method)	7.8	
Pour point	-45	
Sulfated Ash	0.78	
Flash Point COC	225	

Responsible Analist : Marcel Verhoeven

Belgo-American Oil Storage NV

Wijnegembaan 6, Antwerp 2900

TEL : +32 3 658 45 53

E-mail : contact@belcomotoroils.com

www.belcomotoroils.com


BELGO-AMERICAN OIL STORAGE N.V.
Wijnegembaan 6
2900 SCHOTEN